

Input voltage	Output voltage	Output current	Output power	Efficiency	Size
18-35V DC	48V DC	15 Amps	720 Watts	96%	100*80*39mm



### Features


- Design meeting RoHS / CE
- High efficiency: 96% ( @ 24V input )
- Non-isolated between input and output
- Internal capacitor: NCC & NICHICON (high reliability)
- 100% full load burn-in test
- Over load, Over temperature and Over voltage protections
- Waterproof level IP68
- 1 Year warranty

### Applications

- Trucks
- Forklifts
- Buses
- Logging Vehicles
- Electromotor
- Telecommunications
- Boat & Yacht
- LED Marketplaces and so on..

### Model naming method

**WG-24S4815**



### Specifications

Model	WG-24S4815		
Input	Rated voltage	V	24
	Voltage range	V	18-35
	Efficiency (type)	%	96 @ 24V input
	Positive cable (red)	AWG	12 @ 15cm length
	Negative cable (black)	AWG	12 @ 15cm length
Output	Voltage	V	48
	Max. rated current	A	15
	Max. rated power	W	720
	Voltage regulation	%	±1
	Load regulation	%	2
	No load loss	mA	70 @ 24V input
	Ripple & noise	mVp-p	170 (full load)
	Positive cable (white)	AWG	14 @ 15cm length
	Negative cable (black)	AWG	14 @ 15cm length
Environment	Working temperature	°c	-40 ~ +80
	Working humidity	RH	10% ~ 90%
	Storage temperature	°c	-40 ~ +100
Function	Short circuit protection		NO
	Over current protection	A	YES
	Waterproof		IP68
	Over temperature protection		YES
	Over voltage protection		YES
Mechanical	Weight	g	480
	Size	mm	100*80*39
Other	Cooling		Free air convection
	Packaging		White box

### Dimension

100 x 80 x 39 mm

